



# Tekskil Value Series Aux Displays

**Boost production quality with these HD auxiliary displays**  
**A perfect companion for the new generation of Prompter Systems**



This wide screen Aux Display will make life easier for your on-screen talent and production crew. Tekskil's 19VHD and 22VHD mount perfectly with today's smaller, lighter cameras & pan/tilt heads – no problems with overloading or balancing your camera system. The display is mounted at the optimum position and angle underneath the prompter with micro-truss supports - Tekskil's benchmark design and engineering. Our custom hardware enables mounting to any Tekskil Pro or Premium Series Studio Prompters.



19V- HD

22V- HD

Many broadcast studios are realizing the benefits of prompter-mounted Auxiliary Displays - secondary screens are a great way to share remote feeds and on-air cueing with the talent. Server feeds, Chromakeys, and over-the-shoulder inserts are readily visible without losing eye contact with the camera. Your talent will appreciate the added production support provided by auxiliary displays. These High Definition LED Backlit LCD units are comfortably viewed from 25+ feet away. These are an extremely cost-effective addition to the camera platform. Compare features, construction and value with other manufacturers - Tekskil's quality, ease of use and affordability make our prompting systems the best choice for all your prompting needs.

### Features of the 19 and 22 inch Aux

- Edge lit **LED** Backlight Technology
- Sharp Quattron™ quad pixel technology
- Low reflectance imaging
- Slim light weight cabinet with robust truss mounts for correct, secure positioning
- 16 x 9 Aspect Ratio
- Side Bar, Zoom and Stretch Modes
- Very low power consumption

Compare Tekskil's stabilized rigid truss design with the competitions articulated arms. What do you want suspending your Talent Assist/Aux Panels?



### Specifications

	<u>19VHD-A</u>	<u>22VHD-A</u>
Panel Type:	Active Matrix TFT LCD	Active Matrix TFT LCD
Active Screen Size	18 1/2 inches Diagonal	21 1/2 inches Diagonal
Pixel Format (RGB):	1366 x 768 (Native Resolution)	1920 x 1080 (Native Resolution)
High Definition Inputs:	HDMI & Component Video Y/Pr/Pb	HDMI & Component Video Y/Pr/Pb
Standard Definition Inputs:	Composite & 'S' Video	Composite & 'S' Video
Contrast Ratio:	20,000:1	20,000:1
HDTV Resolutions:	720P 1080i @120Hz	720P 1080i 1080P @120Hz
Response Time:	5 msec	5 msec
Viewing Angle ( H / V ):	170° / 160°	170° / 160°
Panel Weight:	7.2 lbs	8.8 lbs
LED Lamp Life:	50,000-Hour	50,000-Hour
Power Consumption:	28 Watts (120 VAC)	34 Watts (120 VAC)

### Need SDI Inputs?

#### SD/HD-SDI to HDMI Mini Converter



Economical Mini SDI to HDMI video converter allows you to easily connect HDMI displays to SDI based equipment

**Set up one of our systems in your studio and see the difference for yourself**

## Tekskil Industries, Inc.

Phone: 604-985-2250  
 Visit our website at [Tekskil.com](http://Tekskil.com)

Toll Free 877-TEKSKIL (835-7545)

Toll Free Fax: 877-576-8361  
 Email: [TekskilPrompters2011@tekstil.com](mailto:TekskilPrompters2011@tekstil.com)